

CLASS "B" CARGO PANT

- DESIGN** Cargo-style pant with five flat pockets (no pleats).
- FABRIC** 65/35 Polyester/Cotton.
- COLOR** CDC approved Olive Green (United-Avondale, Pro-Turf-Milliken #02552, or equivalent.)
- POCKETS** All pockets and pocketing are to be of body fabric.
- Back Two rear hip patch pockets finished to 6.5 X 6.5 inches, with a ¾ inch double fold hem.
- Front Two slash-style (quarter top style) front bag pockets. Cut from trouser material with a minimum of 6.5 inches.
- Side Two thigh pockets measuring 8.25 x 10.25, finished at 7.25 x 9.25 with covered diagonal zippers, (7 inches – 8 inches) closed in the downward direction and toward the inseam on each leg positioned 4 inches below the bottom of the opening of the bag pocket.
- Calf One 5.75 x 12 pocket finished to 4.75 x 11 with a 5" covered zipper placed vertically in the center beginning 2 inches down from the top of the unfinished pocket. Pocket placement is to be on the right out seam 5" below the bottom of the thigh pocket. Or, one 8.25 square pocket finished to 7.25 square with a 7 inch covered zipper placed diagonally and closing in the downward direction beginning 1 inch below the top of the pocket.

ZIPPER/FLY

BELT LOOPS

Are to be 3/8 to 3/4 inch wide, (3/4 inch is recommended) of two plies folded, finished on the underside, and top stitched 3/16 inch from each edge. There will be seven belt loops, one centered at the back of the seam, two to be placed just forward of the side seams, and the other four loops to be evenly spaced between these loops. The loops are to be tall enough to accommodate a 2 inch duty belt and sewn into the waistband at both the top and bottom.

TROUSER CREASE

Front and back creases are to be permanently set with steam press and Creaset™ system, or equivalent, prior to the double knees applied.

KNEES

Double knees of the same fabric as the pant will be placed on each knee area measuring the width of the pant leg and 10 inches in height. The top seam is approximately 9-1/2 inches below the crotch seam.

MANUFACTURERS: Fechheimer, or United Uniform Manufacturers, Inc.

CLASS "B" SHORT SLEEVE SHIRT

COLOR Silvertan

STYLE The style shall be known as a convertible collar, short sleeve, and coat shirt, with full length tail and form-fitting. The shirt is to have outside breast pockets and scalloped flaps having one button each. Also to have full badge sling and shoulder straps. The back is to have a double yoke, with high luster polyester/cotton poplin band and yoke trim.

COLLAR Convertible collar shall be one piece and measure 3-1/4" long at points. The collar shall be made with permanent collar stays. Collar is to be topstitched 1/4" off the edge. To be interlined with #285 Mellopress.

FRONT The left front shall have a top center 1-1/2" wide with two double rows of stitches. The shirt will have seven buttons and buttonholes on the front, spacing between each will be 3-3/4". Top center to be interlined with #550 Mellopress.

SHOULDER STRAPS

Style and dimensions as sample. Asymmetrical shape, topstitched 1/4" off the edge to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" set not more than 1/2" from folded collar. Cross stitched approximately 2" from sleeve seam. Crossed and edge stitched shoulder strap construction unacceptable.

BADGE REINFORCEMENT

Exterior holder to finish 1-1/8" wide by 2-1/4" deep, with two metal eyelets spaced 1-1/8" apart with button eyelet centered 1-1/2" above left flap.

POCKETS

Two plain breast pockets. Pockets to measure 5-5/8" wide, 6" deep. Left breast pocket to have 1-1/2" pencil stitch. Women's shirt pockets will be 5" wide, 5" deep. Each pocket to have Velcro tape 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as sample.

FLAPS

Deep scalloped design to measure 6 1/4" across, 2-3/4" in depth at center point. Secured to shirt front approximately 1/4" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. Both flaps to be interlined with #550 Mellopress. Creased and edge stitched pocket flap construction unacceptable.

Underside of the flap to have Velcro tape 3/4" long by 1/2" wide positioned on outer points of both pocket flaps as sample.

MILITARY CREASES

Seven baked-in sharp military creases on all shirts. One crease on each front to be centered vertically through pockets and flaps. Spacing for military creases on shirt back to be proportionate to the size of the shirt.

EXAMPLE OF CLEAR RAIN COAT AND PANTS

